12. (Twice Amended) A method of manufacturing the inkjet head according to claim 1, comprising the steps of:

forming a metal layer on a nozzle surface of a nozzle member; and immersing said nozzle member on which said metal layer has been formed in a solution in which a polycyclic thiol compound has been dissolved.

REMARKS

Claims 1-13 are pending. By this Amendment, claims 1-12 are amended. No new matter is added.

In view of the foregoing amendments and remarks, Applicants submit that this application is in condition for allowance. Favorable reconsideration and prompt allowance of claims 1-13 are earnestly solicited.

Should the Examiner believe that anything further would be desirable in order to place this application in better condition for allowance, the Examiner is invited to contact Applicants' undersigned representative at the telephone number set forth below.

Respectfully submitted,

James A. Oliff

Registration No. 27,075

Eric D. Morehouse Registration No. 38,565


JAO:EDM/gam

Attachment:

Appendix

Date: April 2, 2003

OLIFF & BERRIDGE, PLC P.O. Box 19928 Alexandria, Virginia 22320 Telephone: (703) 836-6400 DEPOSIT ACCOUNT USE
AUTHORIZATION
Please grant any extension
necessary for entry;
Charge any fee due to our
Deposit Account No. 15-0461



APPENDIX

Changes to Claims:

The following are marked-up versions of the amended claims:

- 1. (Amended) An ink jet printer headinkjet head, wherein ink drops are ejected from nozzles formed in a nozzle surface, comprising:
- a metal layer comprising metal formed on said nozzle surface; and
 a self-organized film layer consisting essentially of a polycyclic thiol
 compound formed on a top of said metal layer.
- 2. (Amended) The ink jet printer headinkjet head according to claim 1, wherein an intermediate layer consisting of nickel, chromium, tantalum or titanium, or an alloy thereof, is provided between a member that forms said nozzle surface and said metal layer.
- 3. (Twice Amended) The ink jet printer headinkjet head according to claim 1, wherein said self-organized film layer is formed on inner walls of said nozzles.
- 4. (Twice Amended) The ink jet printer headinkjet head according to claim 1, wherein said nozzles are provided in indented sections provided in said nozzle surface.
- 5. (Twice Amended) The ink jet printer headinkjet head according to claim 1, further comprising cavities into which ink is filled and pressure-applying devices that produce volume changes in said cavities, wherein ink drops are ejected from said nozzles through said volume changes in said cavities.
- 6. (Amended) The ink jet printer headinkjet head according to claim 5, wherein said pressure-applying devices are piezoelectric elements.
- 7. (Amended) The ink jet printer headinkjet head according to claim 5, wherein said pressure-applying devices are heat-generating elements.

8. (Twice Amended) The ink jet printer headinkjet head according to claim 1, wherein said polycyclic thiol compound is a compound represented by undermentioned general formula (I) or (II):

wherein Cf is $CF_3(CF_2)_n$, $CF_3(CF_2)_n(CH_2)_{mb}$ (CF_3)₂ $CF(CF_2)_n$, (CF_3)₂ $CF(CF_2)_n(CH_2)_{mb}$ (CF_3)₃ $C(CF_2)_n$ or (CF_3)₃ $C(CF_2)_n(CH_2)_{mb}$ n is an integer greater than or equal to 0, m is an integer greater than or equal to 1, k is an integer greater than or equal to 3, p is an integer greater than or equal to 1, and 1 is an integer from 1 to 4.

- 9. (Amended) The ink jet printer headinkjet head according to claim 8, wherein, in said general formula (I) or (II), Cf is CF₃(CF₂)_n or CF₃(CF₂)_n(CH₂)_m, n is an integer from 0 to 15, m is an integer from 1 to 20, k is 3 or 4, p is an integer from 1 to 20, and 1 is an integer from 1 to 4.
- 10. (Amended) The ink jet printer headinkjet head according to claim 8, wherein, in said general formula (I) or (II), Cf is (CF₃)₂CF(CF₂)_n or (CF₃)₂CF(CF₂)_n(CH₂)_m, n is an integer from 0 to 15, m is an integer from 1 to 20, k is 3 or 4, p is an integer from 1 to 20, and 1 is an integer from 1 to 4.
- 11. (Amended) The ink jet printer headinkjet head according to claim 8, wherein, in said general formula (I) or (II), Cf is $(CF_3)_3C(CF_2)_n$ or $(CF_3)_3C(CF_2)_n(CH_2)_m$, n is an integer from 0 to 15, m is an integer from 1 to 20, k is 3 or 4, p is an integer from 1 to 20, and 1 is an integer from 1 to 4.

Docket No. 110085

12. (Twice Amended) A method of manufacturing the ink jet printer headinkjet head according to claim 1, comprising the steps of:

forming a metal layer on a nozzle surface of a nozzle member; and immersing said nozzle member on which said metal layer has been formed in a solution in which a polycyclic thiol compound has been dissolved.